HYDRAULIC TILT BUCKET

PRODUCT FEATURES

- 30" 36" 42" 50" 54" 60" and 36" Deep Profile sizes available
- Plug and play setup
- Mount and hoses included
- 45 degree tilt in both directions
- Bolt-on, reversible, HARDOX cutting edge with recessed bolts
- Sizes 36" and up have dual tilt cylinders
- Sizes 36" and up have a welded on, back grading edge





Whether you are digging pools, ponds, sidewalks, foundations, hardscapes, utility trenches, swales, or drainage ditches the Mongo Attachments Hydraulic Tilt Bucket will get the job done faster and more precisely. Mongo tilt buckets come ready to use, with the appropriate length hoses and flat-face couplers included.

PRODUCT SPECIFICATIONS

	Photo	Compatible Machine Size	Weight Without Mount	Struck Capacity	Heaped Capacity (SAE)
30" Tilt Bucket		1.5 - 2 T	250 lbs	2.0 cu-ft	2.6 cu-ft
* 36" Tilt Bucket		2.5 - 4.5 T	300 lbs	2.5 cu-ft	4.1 cu-ft
* 42″ Tilt Bucket		3.5 - 5 T	400 lbs	2.8 cu-ft	4.8 cu-ft
* 50" Tilt Bucket		5 - 10 T	580 lbs	5.6 cu-ft	8.8 cu-ft
* 60" Tilt Bucket		7.5 - 10 T	650 lbs	7 cu-ft	10.8 cu-ft
* 36" Deep Tilt Bucket		5 - 10 T	600 lbs	5.6 cu-ft	8.9 cu-ft
* 54" Tilt Bucket		Up to 16 T	1040 lbs	13.5 cu-ft	18.9 cu-ft

^{*} Welded on HARDOX back grading edge and dual tilt cylinders