PROGRADE FORESTRY MULCHERS

PROFESSIONAL FIXED-TOOTH MULCHER FOR MAXIMUM OUTPUT & JOB QUALITY

The Mongo Attachments ProGrade Forestry Mulchers expand on our proven mulching technology, delivering superior efficiency and power for demanding land-clearing operations. Designed for excavators from 7,000 lbs and up, these mulchers feature an optimized bite-limiting design, maintaining peak rotor RPMs with hydraulic flow as low as 17 GPM.

- Easy-tune hydraulic system
- Commercially available teeth
- Precision Balanced Drum
- Best in class access panels
- Offset drum for laterally addressing trees
- High efficiency bite limiter drum
- Integrated kickstand for easy storage
- Manually adjustable rear discharge gate
- Heavy-duty, rigid chassis
- Thumb saddles are available for all sizes and are sold separately (adds 143 lbs)
- Machine-specific coupler and hoses included

PRODUCT SPECIFICATIONS

MODEL	WEIGHT WITHOUT MOUNT	MOTOR	MOTOR SIZES (CC)	OIL FLOW (GPM)	PSI RATING (WHILE FLOWING)	RPM RANGE	MINIMUM EXCAVATOR WEIGHT	# OF TEETH	CUTTING WIDTH	CUTTING DIAMETER
MPG70R-26	864 lbs	Gear Motor Cast Iron	26	17-19	3,100	2,400-2,600	3.5 T	16	27"	5"
MPG70R-31	864 lbs	Gear Motor Cast Iron	31	19-22	3,100	2,400-2,600	3.5 T	16	27"	5"
MPG90R-36	981 lbs	Gear Motor Cast Iron	36	22-24	3,100	2,400-2,600	6 T	20	35"	6"
MPG105R-41	1,058 lbs	Gear Motor Cast Iron	41	25-26	3,100	2,400-2,600	8.5 T	24	41"	6"